



PRECISION CLEANING SYSTEM SERIES

T-5000-PCS, T-6000-PCS and T-7000-PCS

SPECIFICATIONS

STANDARD FEATURES

Purifier Filtration System
Front Loading Hinged Door Models
Load Bearing/Safety
Vertical (Seal-less) Pumps
Turntable/Basket/Drive System
Spray Manifolds
LWS-F1 Water Level Controls

SEVEN PCS UPGRADES

Stainless Steel
Two Integrated Tanks
High Volume Rinsing
Drying (Optional)
Deluxe Control System
Full Cabinet Insulation
PCS Training Support

OPTIONAL FEATURES

ARC-22 Rinse System
ILF-22 Micro Filter
ASX-11 Steam Exhaust Systems
Allen Bradley "Panelview 500" Processer
RCB-11 Coated Baskets
SPB-11 Small Parts Basket
SST-11 Side Tray
Jet Washing Detergents

FEATURE	T-5000-PCS	T-6000-PCS	T-7000-PCS
Turntable Diameter	50" *	60" *	70" *
Working Height	27"	27"	27"
Turntable Area	1970 sq. in.	2830 sq. in.	3860 sq. in.
Weight Capacity	1,500 lbs.	2,500 lbs.	2,500 lbs.
Vertical (seal-less) Pump	7.5 HP	10 HP	10 HP
Pump Output	150 GPM/60 PSI	200 GPM/60 PSI	200 GPM/60 PSI
Tank Size	175 gal / tank	225 gal / tank	275 gal / tank
Heat	27 kW / tank	36 kW / tank	36 kW / tank
Heat-up Time	1.5 hours	1.5 hours	1.5 hours
Electric Power	460V / 3-Phase	460V / 3-Phase	460V / 3-Phase
Full Load Amps	83	108	108
Overall Dims	80" (w) x 100" (d) x 62" (h)	90" (w) x 110" (d) x 62" (h)	100" (w) x 120" (d) x 62" (h)
* Reduce by 2.5" for clear loading of single largest part.			

LIFETIME GUARANTEE against any welds cracking or leaking *

LIFETIME GUARANTEE on the turntable and its sealed bearing assembly

LIFETIME GUARANTEE against the door ever jamming

* Warranty void if leaks caused by corrosion



T-5000-PCS



T-5000-PCS